

## Rotary Screw Air Compressors VS Series™



### 80–110 kW, VS 80/110 Variable Speed Control

#### Efficiency

The VS series from Gardner Denver is the newest generation of variable speed rotary screw compressors. The ENDURO®+ air end ensures that maximum reliability and the highest efficiency level are incorporated into these packages. The VS Series utilizes a rotor profile improvement that results in the lowest specific power over the widest operating range. We have minimized energy consumption throughout the entire package to bring you the lowest possible energy cost of operation.

#### Flexibility

The modern VS Series compressor packages are the *smarter solution* to your complex air system needs. The AirSmart™ controller maintains a target pressure band of +/- 1 psig through the entire operating range of 100%–20% of the compressor's capacity. The variable speed drive/motor/compressor combination and the controller are designed to meet the varying demands of your system at the lowest possible specific power (kW/100 CFM), which benefits you in the form of energy cost savings.

#### Serviceability

The design of these packages assures the service points are readily accessible. The inlet valve is easy to access and has a simple design that minimizes the number of moving parts resulting in lower maintenance costs. The enclosure side doors are hinged and removable to allow complete access to all service points.

#### Proven Technology

Gardner Denver leads product development with new technologies such as Computational Fluid Dynamics, Finite Element Analysis and Infrared Thermography. These tools allow Gardner Denver to design and build smarter solutions to the complex needs of today's compressed air systems. With this technology, we have been able to simultaneously develop an efficient, flexible, reliable, compact and serviceable compressor.



Experience Proven Results

# Technical Data—VS Series™

## VS 80/110, 60 Hz



Gardner Denver Model	Rated Pressure		Capacity at Rated Pressure*		Motor power kW	Net weight		Air Outlet Size NPT	Noise level** dBA
	psig	bar	acfm	m <sup>3</sup> /min		lbs	kg		
VS 80	100	7.0	558	15.8	80	6,100	2,767	2.0"	72
	125	8.6	506	14.3					
	150	10.3	462	13.1					
	175	12.1	417	11.8					
VS 110	100	7.0	719	20.4	110	6,200	2,812	2.0"	76
	125	8.6	663	18.8					
	150	10.3	603	17.1					
	175	12.1	560	15.9					

\* Capacity measured in accordance with CAGI/PNEUROP acceptance test code PN2CPTC2.

\*\* Noise level measured in accordance with ISO 2151.

### Standard Equipment

- Air inlet filters
- Fully automatic capacity control: variable speed air production based on system air demand
- Gardner Denver AirSmart™ controller
- Easy to use operator interface
- Multiple languages
- High efficiency AC inverter drive
- TEAO electric motors: IP 55, F-class insulation and unlimited start/stop capability
- Smart thermal mixing oil control valve

- IP 54 control enclosure
- Emergency stop
- Safety devices for
  - Motor over temperature
  - Compressor over temperature
  - Compressor over pressure
  - Current limiter
- Alarms for
  - Air inlet filter ΔP
  - Oil separator element ΔP
  - Compressor over temperature (alarm at 107°F and tripping at 115°F)
  - Service interval
- Pressure relief valve

- Running condition indicators:
  - Pressures
  - Temperatures
  - Hour meter; total running hours, full load hours
- Automatic re-start after power failure
- Powder coated enclosure
- After cooler and moisture separator with automatic zero loss drain
- ENDURO®+ air end
- Air or water-cooled cooling with 15°F CTD after cooler approach temperature

### Optional Equipment

- EMC filter
  - Multiple lubricant options
  - Line reactor
  - Communications/Sequencing module
  - Saltwater cooler
  - Seacoast cooler
  - Auto water temperature regulator
  - Water flow regulating valve
- ### Auxiliary Equipment
- Multi-compressor controller for several compressors
  - Compressed air after treatment products

# Gardner Denver®

For additional information contact your local representative or Gardner Denver Compressor Division, 1800 Gardner Expressway, Quincy, IL 62305  
 Customer Service Department Telephone: (800) 682-9868 FAX: (217) 224-7814  
 Sales and Service in all major cities.  
[www.GardnerDenverProducts.com](http://www.GardnerDenverProducts.com) [maggie@gardnerdenver.com](mailto:maggie@gardnerdenver.com)

©2007 Gardner Denver, Inc. Litho in U.S.A. GS-VS-80-110 1st Ed. 12/07

